

**727630C**

FallTech® Contractor C SRL with 30' Galvanized Cable and Anchorage Carabiner

**Features :**

- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook
- Features glass-filled nylon housing for durable impact resistance.
- Lifeline includes recoil spring bumper to reduce retraction lock-up
- Rugged internal steel drum and inertial braking system deliver reliable performance
- SRL includes double-locking twist-lock anchorage carabiner
- Complies with ANSI Z359.14-2014



Material Specifications		Performance Specifications		Compliant With:	
<b>Cable</b>	3/16" galvanized steel; 3,400 lb min. static strength	<b>Static Strength</b>	3,000 lb min.	<b>ANSI</b>	Z359.14-2014
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>ANSI SRL Class</b>	Class B	<b>OSHA</b>	1926.502 and 1910.66
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Avg. Arrest Force</b>	900 lb		
		<b>Max. Arrest Force</b>	1,800 lb		
		<b>Max. Arrest Distance</b>	54"		
		<b>ANSI User Capacity</b>	130 to 310 lb max.		
		<b>OSHA User Capacity</b>	130 to 310 lb max.		

Sizes & Part Numbers					
727620 -20' (ANSI Compliant)	727630C - 30' (ANSI Compliant)	C727630 - 30' (CSA Compliant)	727650C - 50' (ANSI Compliant)	C727650 - 50' (CSA Compliant)	7276100 - 100' (ANSI Compliant)



**SALES • RENTAL • SERVICE**  
 353 S. Central Avenue, Los Angeles, California 90013  
 800-992-0100 stemarinc.com