



BLOWER HOSES & COUPLERS

SPECIFICATIONS



BLOWER HOSES

SIZE x LENGTH	STEMAR Rental Class No.	STEMAR Sales Item No.
8"x25'	8617	BLOWER201
12"x25'	8619	BLOWER203
12"x50'	-	BLOWER202
16"x25'	8624	BLOWER204
20"x25'	8626	BLLOWER208
26"x25'	9001	BLOWER207

FEATURES

- Heavy Duty Construction
- Spiral Wire Reinforcement
- High Retraction Ratio
Minimizes Storage Size
- Attach Strap and Nylon
Ring End Cuffs

SPECIFICATIONS

	STANDARD	REFERENCE
Tensile Strength	Warp 125/Fill 110	FED STD 191-5100
Tear Strength	Warp 41/Fill 36	FED STD 191-5513
Temperature Range	-20°F to +180°F (-29°C to +82°C)	
Flame Resistance	California T-19; UL94VO; UL94VTM-0; NFPA 701	
Ozone Protection	Inherently resistant to deterioration	
Operating Environment	Nonhazardous Type Locations	
Nominal Diameters	8 inches (203 mm) and 12 inches (305 mm)	

STEMAR BLOWER / DUCTING HOSES

Available in 25' lengths for each model, our ducting is made of flexible, light duty vinyl woven polyester.

Each duct easily expands and retracts and is designed to handle large volumes of air at relatively low pressure.

STEMAR's ducting is flame-retardant and connects easily to the ventilators for both positive and/or negative airflow.



DUCT COUPLERS

When connecting one piece of duct to the next, use these galvanized corrosion resistant couplers to achieve any length desired.